Mounting Clamp Assembly

Eye-Bolt For Lifting

120 in.

6 in.

60.2 in.

192.2 in.

BALL STRIKE OUT

1 2 3 4 5 6 7 8 9 RUNS

Cabinet Size, Weight:
16 ft. x 5 ft., 300 lbs.

Electrical Requirements:
5.0 Amps, 120 VAC

Display Sizes:
15 in. tall Ball
15 in. tall Strike
15 in. tall Out
15 in. tall 3-Digit Game Clock (H:MM)
11 in. tall Home Total Runs
11 in. tall Guest Total Runs
11 in. tall Home Runs-By-Inning (1-9)
11 in. tall Guest Runs-By-Inning (1-9)
4 in. tall Activity Indicator
7 in. tall 9 x 56 pixel ETNs

Standard Post Sizes:
2 each, max diameter 7 in.

Standard Equipment & Features

• Single cabinet design with heavy duty extruded aluminum framing
• Light weight, rust free, all aluminum construction
• Mounting hardware for permanent installation on posts without the need for on site fabrication
• Automotive grade baked on enamel based paint applied to the scoreboard face
• Choice of 18 standard paint colors
• Choice of amber or red LED displays
• LED display circuit boards conformal coated for outdoor use
• Full-sized 37-key control console with LCD display
• Fifty programmable brightness levels
• Junction box and patch cable for hardwired installations
• Five-year limited warranty
• Toll free technical support via phone and online for the life of the product

Optional Equipment & Features

• ID panels with custom graphics, in a variety of sizes, shapes and styles, to mount above or below the scoreboard
• Extended configurations for ID panels built into the left or right side of the scoreboard cabinet
• Full color video and other electronic display panels
• Stadium Sound System packages
• Custom paint colors
• Up to 1,000 feet of data cable for hardwired installations
• ScoreLink Wireless RF modem system for wireless communication
• Additional warranty and support plans

TDD/ Rev 2012-Oct.