



Cabinet Size, Weight:  
20 ft. x 6 ft., 350 lbs.

Electrical Requirements:  
3.8 Amps, 120 VAC

Display Sizes:  
15 in. tall 4-Digit Game Clock (MM:SS)  
15 in. tall Ball  
15 in. tall Strike  
15 in. tall Out  
15 in. tall H/E Indicators  
15 in. tall Error Fielder Position  
11 in. tall Home Runs-By-Inning (1-10)  
11 in. tall Guest Runs-By-Inning (1-10)  
11 in. tall Home Total Runs  
11 in. tall Guest Total Runs  
11 in. tall Home Total Hits  
11 in. tall Guest Total Hits  
11 in. tall Home Total Errors  
11 in. tall Guest Total Errors

Standard Post Sizes:  
2 each, max diameter 7 in.

Standard Equipment & Features

- Single cabinet design with heavy duty extruded aluminum framing
- Light weight, rust free, all aluminum construction
- Mounting hardware for permanent installation on posts without the need for on site fabrication
- Automotive grade baked on enamel based paint applied to the scoreboard face
- Choice of 18 standard paint colors
- Choice of amber or red LED displays
- LED display circuit boards conformal coated for outdoor use
- Full-sized 37-key control console with LCD display
- Fifty programmable brightness levels
- Junction box and patch cable for hardwired installations
- Five-year limited warranty
- Toll free technical support via phone and online for the life of the product

Optional Equipment & Features

- Electronic Team Names
- ID panels with custom graphics, in a variety of sizes, shapes and styles, to mount above or below the scoreboard
- Extended configurations for ID panels built into the left or right side of the scoreboard cabinet
- Full color video and other electronic display panels
- Stadium Sound System packages
- Custom paint colors
- Team name in place of HOME
- Up to 1,000 feet of data cable for hardwired installations
- ScoreLink Wireless RF modem system for wireless communication
- Additional warranty and support plans