


**MODEL LX1632-ETN**  
Outdoor  
Baseball / Softball



Dimensions	Weight	Cabinet Material	Caption Height	Accent Material
22 ft x 6-1/2 ft	450 lb	Aluminum	7 in, 6 in	2.4 mil cast vinyl
Digit Height	Indicator Size	Digit Colors	Electrical	
18 in, 15 in	4 in	Amber or Red	7.1 Amps, 120 VAC	

**STANDARD EQUIPMENT & FEATURES**

- Single cabinet design with heavy duty extruded aluminum framing
- Light weight, rust free, all aluminum construction
- Mounting hardware for permanent installation on posts without the need for on site fabrication
- Automotive grade baked on enamel based paint applied to the scoreboard face
- Choice of 18 standard paint colors
- Choice of amber or red LED displays
- LED display circuit scoreboards conformal coated for outdoor use
- Full-sized 37-key control console with LCD display
- Fifty programmable brightness levels
- Junction box and patch cable for hardwired installations
- Five-year limited warranty
- Toll free technical support via phone and online for the life of the product

**OPTIONAL EQUIPMENT & UPGRADES**

- ID panels with custom graphics, in a variety of sizes, shapes and styles, to mount above, below, or beside the scoreboard
- Extended configurations for ID panels built into the left or right side of the scoreboard cabinet
- Full color video and other electronic display panels
- Stadium Sound System packages
- Custom paint colors
- Up to 1,000 feet of data cable for hardwired installations
- ScoreLink Wireless RF modem system for wireless communication
- Additional warranty and support plans

**ELECTRONIC TEAM NAMES (ETNs)**

- 7-inch character height
- 9 x 64 pixel matrix
- Three character fonts
- Up to 13 characters per team

**DIGITS / INDICATORS**

Ball, Strike, Out, and Timer digits are 18 inches tall, while all other digits are 15 inches tall. Digits, ETN characters, and indicators are formed from matrices of super-bright, long-lasting, energy-efficient LEDs (Light Emitting Diodes). Choose either amber or red LEDs for all outdoor products. Our LED assemblies are protected by aluminum masks that allow the hard epoxy shells of the LEDs to be exposed for maximum viewing angles.

**PAINT COLOR OPTIONS**

