


MODEL LX1782-ETN

Outdoor Baseball / Softball



Dimensions	Weight	Cabinet Material	Caption Height	Accent Material
36 ft x 10 ft	1100 lb	Aluminum	12 in, 7 in	2.4 mil cast vinyl

Digit Height	Indicator Size	Digit Colors	Electrical
24 in, 18 in, 15 in	15 in, 4 in	Amber or Red	13.6 Amps, 120 VAC

STANDARD EQUIPMENT & FEATURES

- Double cabinet design with heavy duty extruded aluminum framing
- · Light weight, rust free, all aluminum construction
- Mounting hardware for permanent installation on posts without the need for on site fabrication
- Automotive grade baked on enamel based paint applied to the scoreboard face
- · Choice of 18 standard paint colors
- · Choice of amber or red LED displays
- LED display circuit scoreboards conformal coated for outdoor use
- · Full-sized 37-key control console with LCD display
- Fifty programmable brightness levels
- Junction box and patch cable for hardwired installations
- · Five-year limited warranty
- Toll free technical support via phone and online for the life of the product

OPTIONAL EQUIPMENT & UPGRADES

- ID panels with custom graphics, in a variety of sizes, shapes and styles, to mount above, below, or beside the scoreboard
- · Full color video and other electronic display panels
- · Stadium Sound System packages
- Custom paint colors
- Up to 1,000 feet of data cable for hardwired installations
- ScoreLink Wireless RF modem system for wireless communication
- Additional warranty and support plans

ELECTRONIC TEAM NAMES (ETNs)

- 11-inch character height
- 14 x 112 pixel matrix
- · Three character fonts
- · Up to 12 characters per team

DIGITS / INDICATORS

Ball, Strike, Out, and Timer digits are 24 inches tall. Indicators for Hit and Error along with the Error Fielder Position digit are 15 inches tall. All other digits are 18 inches tall. Digits, ETN characters, and indicators are formed from matrices of super-bright, long-lasting, energy-efficient LEDs (Light Emitting Diodes). Choose either amber or red LEDs for all outdoor products. Our LED assemblies are protected by aluminum masks that allow the hard epoxy shells of the LEDs to be exposed for maximum viewing angles.

PAINT COLOR OPTIONS

