

SECTION 116643

MODEL 2577 INDOOR SCOREBOARD

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Single-face electronic scoreboard and control console for indoor use.

1.02 REFERENCES

- A. Standard for Electric Signs, UL-48, 14th Edition.
- B. Standard for Control Centers for Changing Message Type Signs, UL-1433, 4th Edition.
- C. Federal Communications Commission Regulation Part 15.
- D. National Electric Code.

1.03 SUBMITTALS

- A. Scoreboard owner's handbook provides drawings and other information needed for installation, operation, and maintenance of the scoreboard and accessories.

1.04 QUALITY ASSURANCE

- A. Source limitation: Obtain all components including scoreboard, control consoles, data cable, mounting hardware, and other accessories from a single manufacturer.
- B. Manufacturer qualifications: Require company specializing in manufacturing electronic scoreboards with a minimum of ten years experience.
- C. Adherence to nationally recognized standards.
 - 1. ETL listed to UL Standards 48 and 1433.
 - 2. NEC compliant.
 - 3. FCC compliant.
- D. For indoor use only.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Product delivered to installation site unless otherwise specified.
- B. Scoreboard and accessories to be stored in a clean, dry environment.
- C. Special precautions for the scoreboard face.
 - 1. The scoreboard face will be protected during shipment by a layer of cardboard or other sheet material. Avoid removing this protective sheet until the installation begins.
 - 2. Never lay the scoreboard face down or stack other objects on a scoreboard lying on its back.
 - 3. Avoid sliding objects (like another scoreboard) along the plane of the scoreboard face even if the protective sheet is in place. This can result in LEDs being sheared.

1.06 PROJECT CONDITIONS

- A. Scoreboard and accessories should not be installed until the area has been made weatherproof.
- B. The customer determines location of scoreboard, control consoles, and other accessories.
- C. The customer is responsible for verifying that the mounting structure is capable of supporting the weight of the scoreboard, additional panel, and other accessories.
- D. The scoreboard location requires three standard grounded 120 VAC electrical outlets.
- E. The control console location requires three standard grounded 120 VAC electrical outlets.

1.07 WARRANTY

- A. Five year limited warranty includes factory labor and material costs for repairing or replacing defective parts. Refer to the warranty document included in the scoreboard owner's handbook for specific information.
- B. Warranty coverage based on the date of manufacture.

1.08 MAINTENANCE

- A. Replacement parts and factory repair options available from manufacturer.
- B. Product support provided by experienced technicians and online documentation available via phone, web, and email at no cost to customer.

PART 2 PRODUCTS

2.01 MANUFACTURER

- A. Electro-Mech Scoreboard Co., 120 Industrial Parkway, Wrightsville, GA 31096.
 - 1. Phone 800-445-7846.
 - 2. Fax 478-864-0212.
 - 3. Email score@electro-mech.com
 - 4. Click www.electro-mech.com

2.02 SCOREBOARD

- A. General.
 - 1. Functions and Features: Model 2577 Indoor Scoreboard is designed to present information pertinent to basketball and other indoor sports. Presentation includes:
 - a. Four-digit Clock with illuminated colon/decimal indicator that can count up in MM:SS format, count down in MM:SS or SS.T format, or show time of day in HH:MM format. Clock digits are 16 inches tall and made from red LEDs.
 - b. Guest and Home Scores to 199. Score digits are 16 inches tall and made from amber LEDs.
 - c. Period to 9. The Period digit is 12 inches tall and made from green LEDs.
 - d. Guest and Home Bonus/Double Bonus indicators made from green LEDs.
 - e. Guest and Home Next Possession indicators made from red LEDs.

- f. Guest and Home Team Fouls to 19. Digits are 12 inches tall and made from amber LEDs.
- g. Guest and Home Time Outs left to 9. Digits are 12 inches tall and made from red LEDs.
- h. Foul and Point statistics for the five Guest Players and five Home Players currently on the court.
 - 1) Player Number to 99. Digits are 6 inches tall and made from red LEDs.
 - 2) Player Fouls to 9. Digits are 6 inches tall and made from green LEDs.
 - 3) Player Points to 99. Digits are 6 inches tall and made from amber LEDs.
- i. Integrated Horn.
- j. Two dedicated 120 VAC outputs for optional visual horn indicators.
- k. One data output for daisy chaining additional scoreboards or shot timers.
- 2. Cabinet Size: 22 feet (6710 mm) wide, 5 feet (1529 mm) tall, 6 inches (152 mm) deep.
- 3. Cabinet Weight: 280 pounds (127 kg).

2.03 ACCESSORIES

A. Standard accessories.

- 1. Control Consoles.
 - a. The main console supports all features of Electro-Mech 2000 series basketball scoreboards without the need to enter codes or other information to configure the device. The Guest Stat Panel and Home Stat Panel each have a separate console allowing for multiple operators to control the displays.
 - b. The main console provides direct data outputs for up to four scoreboards or shot clocks all synchronized to the data (including the time) generated by the control console. Additional displays may be controlled in synchronization by daisy chaining from the data outputs of scoreboards connected to the main control console.
 - c. Constructed of a heavy-duty ABS plastic housings holding 0.1-inch thick keypad panels with stainless steel metal dome switches that provide tactile feedback and are rated for one million actuations.
 - d. Requires one standard grounded 120 VAC electrical outlet for each console (three total).
- 2. Extension Cable: 10-foot long shielded data cable (one per console) with male stereo connectors at each end allows control consoles to be connected to junction boxes (or ScoreLink transmitters) at the point of operation and later unplugged for storage.
- 3. Junction Boxes: Provide a point of termination for the data cables with a stereo sockets for quick connection to the control consoles.
- 4. Stereo Plugs With Pigtail: Provide connectors to be spliced onto the data cables at the scoreboard end.
- 5. Mounting hardware: The scoreboard cabinet is shipped with two keyhole plates attached to the top rear frame designed to allow the scoreboard to be suspended from lag bolts mounted in the wall. Two eyebolt mounted in the top of the frame may be used to lift the scoreboard cabinet and may also provide a permanent attachment points for suspension cables.

B. Optional accessories.

1. Data Cable: A shielded two-conductor cable with a drain line is the typical means of providing a path for data from the control console to the scoreboard. The Model 2577 uses three control consoles and will therefore require three runs of data cable.
2. ScoreLink Wireless RF Modem System: This RF communications system may be substituted for the data cable at the time of installation or as a replacement for the cable at any time after the installation. ScoreLink requires a standard electrical outlet for the transmitter at the point of operation and another for the receiver at the scoreboard. The Model 2577 uses three control consoles and will therefore require three ScoreLink sets for complete elimination of data cables.
3. ID Panels: This scoreboard may be ordered with an ID panel, shipped as a separate cabinet, to be added along the bottom. ID panels may be purchased blank or with simple text, multi-colored text and graphics, or screen-printed processed-color logos applied to their faces.
4. Carrying Cases For Control Consoles: Included with the ScoreLink system, this option is also available for scoreboards with hard-wired data cables.
5. Handheld Clock Start/Stop Control: Provides a hand-held pendant that allows the clock operator to start and stop the Game Clock without touching the control console.
6. Shot Clock Displays: A pair of these displays can be mounted on the two goals of a basketball court. See our product literature or specifications for Model 2160 and Model 2180 for details.
7. Visual Horn Indicators: Designed to illuminate whenever the scoreboard horn sounds. These indicators must attach to receptacles provided on the scoreboard cabinet.
8. Team Name In Place of "HOME".

2.04 FINISH

- A. Standard scoreboard faces and digit masks are coated with low gloss black polyester resin paint for maximum contrast and resistance to scratches.
 1. Baked on automotive grade low gloss paint in a selection of standard colors is available from the manufacturer for the scoreboard face.
 2. Non-standard colors and finishes may be applied to the scoreboard face at the customer's request.
- B. Scoreboard framing and back are mill-finished aluminum.
- C. Captions and other decorative elements on the face of the scoreboard are vinyl.

2.05 SOURCE QUALITY CONTROL

- A. Tests and inspection.
 1. Manufacturer requires sub-contracted printed circuit board subassemblies to undergo functional testing at the point of manufacture.
 2. Manufacturer inspects incoming components prior to installation in scoreboard and accessories.
 3. Manufacturer functionally tests major electrical subcomponents prior to installation in scoreboard and accessories.

4. Manufacturer inspects and tests scoreboards and accessories at full power prior to shipment.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify 120 VAC outlets at scoreboard and control console locations are properly grounded.
- B. If data cable is used, verify continuity from scoreboard to control console locations.
- C. Verify data cable and AC power cable are not run in the same conduit or wire tray.
- D. Verify data cable and AC power cable are secure and run in conduit where they might be exposed to abuse or where local, state, or national codes require.
- E. Verify location of scoreboard, junction box (or boxes), and accessories with customer.
- F. Test scoreboard and control consoles by attaching each unit to power and plugging console outputs into scoreboard data inputs prior to hanging scoreboard.

3.02 INSTALLATION

- A. Refer to scoreboard owner's handbook for installation instructions.

3.03 PROTECTION

- A. The most common sources of damage to scoreboards and accessories are electrical surges running through power or data connections. The usual causes are lightning, power equipment problems (floating neutrals, bad transformers, etc.), and improper connections. To minimize these problems:
 1. Ensure electrical wiring is properly grounded.
 2. Unplug control consoles from power outlets and from data cables when not in use.
 3. Turn off the breaker to disconnect scoreboard from power when not in use.
 4. Label scoreboard data cable junction boxes and all connectors near junction boxes, scoreboard, and accessories so that public address systems and other devices with similar connections are not accidentally plugged into the scoreboard.
- B. Avoid loss or damage of control consoles, extension cables, and other accessories by storing when not in use.

END OF SECTION